



## **3001 RV AWNING MISTER KIT** **SET UP/ TAKE DOWN GUIDE**

**The following instructions are designed to help you easily set up and take down the RV Awning Mister System.**

### **Set Up Guide**

**STEP 1:** Locate water source of campsite or find an assessable faucet on the RV.

**STEP 2:** Carefully unwind misting line.

**STEP 3:** Find best location for the On/Off valve (it straps to one of the awning supports).

**STEP 4:** The mister head at the end of the misting line should be clipped in place first at the farthest point of the awning and work backwards.

**STEP 5:** Make sure the line is pulled tight to prevent sagging.

**STEP 6:** Adjust mister heads to spray downward.

**STEP 7:** Use straps on each side of On/Off valve to strap the valve on the awning support.

**STEP 8:** Connect Garden Hose Adapter to the campsite spigot (or the end of garden hose). Or follow next few steps in connecting Special T Adapter into the RV's faucet.

**STEP 8a:** To install Special T Adapter into RV, make sure the pressure pump switch is turned off.

**STEP 8b:** Simply use a wrench to disconnect the 1/2" line from the faucet.

**STEP 8c:** Screw 1/2" T Adapter (from Kit) between the line and the faucet (connect to COLD side).

**STEP 8d:** Route misting line from awning and insert the end of the 1/4" tubing into the T Adapter.

**STEP 9:** Turn on water source.

**WHEN YOU WANT THE MISTER TO PROVIDE REFRESHING COOLING MIST, TURN THE "ON/OFF VALVE" IN THE ON POSITION (PARALLEL TO THE LINE).**

**Note: Mister Line should be taken down prior to collapsing RV Awning**

### **Pack Up Guide**

**STEP 1:** Turn OFF the on/off valve.

**STEP 2:** Disconnect Garden Hose Adapter from the water source. Turn ON manual valve let water drain from tubing

**STEP 3:** If you have installed T Adapter, simply disconnect tubing from non-pressure side of the manual valve

**STEP 4:** Let water drain from the tubing.

**STEP 5:** Un-Strap misting tube and Un-Clip mister heads (keep out of dirt)

**STEP 6:** Carefully coil mister tubing into a 12" diameter loop being careful not to pinch tube.

**PUT AWAY UNTIL ANOTHER HOT DAY!**

### **Maintenance**

Included in your mister kit is an extra mister head. If you notice a head not providing a fine mist, turn off mister and replace head with spare mister head. To disconnect, push the ring at mouth of the fitting toward the fitting and simultaneously push/pull the tube out of it. You may need pliers; be careful not to pinch head or tubing.

To clean the head use CLR or Lime Away. Pour a small amount of CLR or Lime Away into a small container enough to cover mister head and follow instructions on bottle for how long to soak. Once head is clean it can be reinserted in the system.

**(407) 695-0958**  
**toll free: (888) MIST 370**



### **Routine Maintenance**

Heads should be routinely cleaned every 3 months or before a long storage using the instructions above, this will prevent the build up of calcium and lime in mister heads.

Questions please refer to website [www.mist-er-comfort.com](http://www.mist-er-comfort.com) or call (888) MIST 370

### **PRODUCT LIMITED WARRANTY**

Mist-er-Comfort warrants that Mist-er-Comfort's products shall be free of defect in materials and workmanship under normal use within the operating specifications for a period of **one (1) year** from the date of purchase provided that:

- A.) The above warranty shall not apply to any such product part thereof which is damaged as a result of neglect, misuse, alteration, accident, normal wear and tear, misapplication, fire, act of God, freezing, hot water, chemical, flammable or salt water;
- B.) Purchaser's exclusive remedies under the above warranty shall be limited to the repair or replacement of the non-conforming product or part(s) thereof, as determined by Mist-er-Comfort.
- C.) Any non-conforming product must be returned to Mist-er-Comfort within one (1) year from its purchase.
- D.) The warranty contained above does not extend to any goods not manufactured by Mist-er-Comfort even though supplied by Mist-er-Comfort. Goods not manufactured by Mist-er-Comfort carry only the warranty (if any) of their makers and the Purchaser is entitled to the benefit thereof only so far as Mist-er-Comfort has the power to transfer it;
- E.) Mist-er-Comfort shall not be liable for any special, indirect, or consequential damages;
- F.) **IMPORTANT NOTE:** Mister Nozzles have orifices as fine as human hair, hence bad water that has sediment and or hard water would drastically affect its performance of the nozzles by getting its orifices clogged.

#### ***BE SURE TO DRAIN TUBING AFTER EACH USE... NOT DOING SO WILL VOID THE WARRANTY.***

There are no two water sources alike, hence it is the sole responsibility of the customer to protect his or her nozzles from getting clogged by installing the proper sediment or polyphosphate filter upstream from the misters, so they would be protected against sediment and lime buildup (if need be). When several nozzles get clogged together that is an obvious indication the water source is bad. If nozzles are subjected to bad water and they get clogged because of that, the misting system can not be returned. The warranty does not cover clogging due to sediments or lime build-up.

- G.) All our orders are shipped economy class via UPS or USPS. There is an extra charge for Air and Express deliveries.
- H.) Product design can change at anytime without notice.
- I.) Return shipping and handling cost is to the expense of the customer/buyer.

#### **Return defective items to:**

**Mist-er-Comfort Inc.  
5703 Red Bug Lake Road #103  
Winter Springs, FL 32708**

**(407) 695-0958  
toll free: (888) MIST 370**