



PATIO BOOSTER PUMP KIT **INSTALLATION PROCEEDURES**

The following instructions are designed to help you easily install the Patio Booster Pump. The entire kit is a low voltage 12 VDC system. There are three main layout considerations:

1. Location of water source (hose spigot)
2. Location of INDOOR receptacle controlled by light switch
3. Area to be misted

Installing the Enclosure

1. Carefully unpack box and separate packages/items.
2. Locate closest water spigot or hose connect (enclosure must be within 4 feet of spigot or hose).
3. Remove the 4 sealing caps on back of enclosure.
4. Patio Booster Pump Kit needs to be located lower than the misters themselves to allow misting heads to drain when system is turned off.
5. Using a level; mount the enclosure on the wall by either inserting screws in the back box or use enclosed wall mount kit (see specific instructions for mounting kit in packet).
6. Attach the garden hose adapter from kit to hose spigot DO NOT TURN ON WATER at this time!
7. The kit comes with 25 feet of power cord; locate the closest INDOOR receptacle that is controlled by a light switch. If you cannot locate a controlled receptacle; you may consider a wireless remote controlled receptacle found at many retail outlets or on Mist-er-Comfort's website under the patio system.
8. Once wire is in place connect the female connector to male connector of the transformer; DO NOT PLUG INTO RECEPTACLE or WIRELESS REMOTE CONTROLLER at this time

You are now ready to install the Patio Misting Kit. The best time to install tubing is after it has had time to sit out in the sun to expand. Please begin with Patio Misting instructions starting with STEP 4. Make sure you never install a manual On/Off valve as indicated in STEP 3 of Patio Instructions.

Now to install the Patio Misting tubing to Booster Pump Kit

1. Locate hole with grommet in top left side of enclosure.
2. Using a straight edge knife and NOT a scissor, cut the end of the 20' lead tube to appropriate length.
3. Insert the tube into grommet (use WD40 type product on grommet to easy tube installation)
4. Insert tubing into 1/4" pressure fitting, make sure it goes in all the way to prevent leakage, (you'll feel it click into place)
5. Attach tube up the wall.
6. YOUR DONE!

Now you're ready to Get COOL: First turn on the water source then turn on switch that controls the Booster Pump. It may take a few minutes to charge the system with water. Look for leaks if you see any then turn off the switch for pump and then the water and reseal the connections.

(407) 695-0958
toll free: (888) MIST 370



Maintenance

Once a season the filter should be replaced; order replacement filters on line: www.mist-er-comfort.com

Questions please refer to website www.mist-er-comfort.com or call (888) MIST 370

PRODUCT LIMITED WARRANTY

Mist-er-Comfort warrants that Mist-er-Comfort's products shall be free of defect in materials and workmanship under normal use within the operating specifications for a period of **one (1) year** from the date of purchase provided that:

- A.) The above warranty shall not apply to any such product part thereof which is damaged as a result of neglect, misuse, alteration, accident, normal wear and tear, misapplication, fire, act of God, freezing, hot water, chemical, flammable or salt water;
- B.) Purchaser's exclusive remedies under the above warranty shall be limited to the repair or replacement of the non-conforming product or part(s) thereof, as determined by Mist-er-Comfort.
- C.) Any non-conforming product must be returned to Mist-er-Comfort within one (1) year from its purchase.
- D.) The warranty contained above does not extend to any goods not manufactured by Mist-er-Comfort even though supplied by Mist-er-Comfort. Goods not manufactured by Mist-er-Comfort carry only the warranty (if any) of their makers and the Purchaser is entitled to the benefit thereof only so far as Mist-er-Comfort has the power to transfer it;
- E.) Mist-er-Comfort shall not be liable for any special, indirect, or consequential damages;
- F.) **IMPORTANT NOTE:** Mister Nozzles have orifices as fine as human hair, hence bad water that has sediment and or hard water would drastically affect its performance of the nozzles by getting its orifices clogged.

BE SURE TO DRAIN TUBING AFTER EACH USE... NOT DOING SO WILL VOID THE WARRANTY.

There are no two water sources alike, hence it is the sole responsibility of the customer to protect his or her nozzles from getting clogged by installing the proper sediment or polyphosphate filter upstream from the misters, so they would be protected against sediment and lime buildup (if need be). When several nozzles get clogged together that is an obvious indication the water source is bad. If nozzles are subjected to bad water and they get clogged because of that, the misting system can not be returned. The warranty does not cover clogging due to sediments or lime build-up.

- G.) All our orders are shipped economy class via UPS or USPS. There is an extra charge for Air and Express deliveries.
- H.) Product design can change at anytime without notice.
- I.) Return shipping and handling cost is to the expense of the customer/buyer.

Return defective items to:

**Mist-er-Comfort Inc.
5703 Red Bug Lake Road #103
Winter Springs, FL 32708**

**(407) 695-0958
toll free: (888) MIST 370**